



CORALIA L-DAB 32

VISCOSITY GRADE: ISO VG: 32

GENERAL FEATURES:

CORALIA L-DAB Piston Air Compressor Oils are obtained through petroleum processing. They contain ash-free or low-ash additives with anti-oxidation and anti-corrosion properties.

APPLICATION:

CORALIA L-DAB Air Compressor Oils are intended for lubricating piston and rotary vane air compressors demanding drip-feed lubrication and operating under medium-duty conditions. For the assessment of operating conditions (light-duty, medium-duty and heavy-duty), the following should be considered:

- compressor design (stages, cooling type),
- environment conditions (coolant temperature, inlet air temperature),
- operating conditions (continuous or intermittent operation).

STANDARDS, APPROVALS. SPECIFICATION:

PN-91/C-96073

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Unit	Typical values
Kinematic viscosity at 40°C	mm ² /s	30,6
Viscosity index	-	97
Flow temperature	°C	-18
Flash point	°C	220
Ash content	%(m/m)	0,01
Water content	%(m/m)	Not present

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

VERSION:

1 / 2023.07.17

